HP Latex 3200 Printer

Respond fast to urgent needs with versatile HP Latex printing up to 3.2 m (126 in)





Do diverse, high-quality applications

- Versatile HP Latex Technology and HP Latex Optimizer deliver high image quality at speeds up to 77 m² (830 ft²)/hr¹
- Superior indoor quality beats UV²—smooth transitions, sharp image quality, and preserve media texture
- Handle demanding tiling jobs with confidence —color consistency
 ≤ 1 dE2000 (95% of colors) in tiling mode³

Keep production in-house

- Respond to increasingly shorter turnaround times without sacrificing quality
- HP helps keep you up and running with direct support, including HP remote diagnostics⁴
- Stay in control in-plant and online— HP Print Beat application, printer status beacon, HP Latex Mobile⁵

Enable higher profitability

- You can save time and money—with automatic maintenance, no daily printhead maintenance is required
- Minimize labor costs—a single operator can manage up to four printers at the same time
- Reduce media waste—the HP Latex Media Saver preserves up to 1 linear meter each time you load a roll

For more information, please visit hp.com/go/Latex3200

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at hp.com/communities/LKC

Printed in Indoor High Quality mode (6-pass, 6-color, 100%).

² Based on HP internal testing of prints produced using Indoor High Quality mode (6-pass, 6-color, 100%) at 77 m² (830 ft²)/hr compared to similar performance of select UV printers under \$400,000 USD as of March 2017.

³ The color variation inside a printed job, when printed with tiling optimized media, has been measured to be with maximum color difference ≤ 1 dE2000 (95% of colors) in "Optimize for tiling" mode. Tested on Ahlstrom 5087 wallpaper with stable printing condition within a stable media and a nominal printer. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above the specs mentioned. Backlit substrates measured in transmission mode may yield different results.

⁴ HP remote monitoring and diagnostics requires an upgrade to the service contract with HP.

⁵ HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

HP Latex 3200 Printer (3.2 m / 126 in)

End-to-end sustainability—a better approach

HP Latex Technology delivers all the certifications that matter to your operators, your business, and the environment.6



UL ECOLOGO7

Using water-based inks eliminates exposure to inks with hazard warning labels and high solvent concentrations, and simplifies ventilation, storage, and transportation requirements.

HP Latex Inks enable more differentiation—odorless prints go where solvent and UV can't.



UL GREENGUARD GOLD8

HP is designing end-to-end sustainability into large-format printing.





HP Planet Partners Program9 HP Large Format Media take-back program¹⁰

HP Latex Inks

Odorless prints, with scratch resistance comparable to hard-solvent inks on SAV and PVC banner¹¹

HP Latex Optimizer High image quality at high

speed



HP OMAS & spectrophotometer

Reliable print quality—get the color and quality you expect



HP Latex printheads

1200 dpi native resolution high image quality over the life of the printer



High-efficiency curing

Instant dry—prints are completely dry immediately after printing



- ⁶ Based on a comparison of HP Latex Ink technology to competitors with leading market share as of December, 2013 and analysis of published MSDS/SDSs and/or internal evaluation. Performance of specific attributes may vary by competitor and ink technology/formulation.
- ⁷ Applicable to HP Latex Inks. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see ul.com/EL).

 8 Applicable to HP Latex Inks. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are
- certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <u>ul.com/gg</u> or <u>greenguard.org</u>.

 9 Visit hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be
- available in your area. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.
- ¹⁰ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.
- 11 Scratch-resistance comparison based on testing third-generation HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.
- ¹² Printing double-sided backlit applications requires the optional HP Latex 3000 Double-sided Day Night Kit. Front-to-back image registration accuracy of 2 mm or better when using certified PVC banner and paper media, see hp.com/go/mediasolutionslocator.

 3 HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to
- be connected to the Internet.

Automatic maintenance

Automatic drop detection and nozzle replacement







Dual roll spindles

Double throughput when working with rolls up to 1.6 m (63 in)

Ink collector kit (optional)

Print unlined mesh banner and porous textiles



Double-sided day night kit (optional)12

Easily produce double-sided backlit applications for color-accurate outdoor advertising displays in any light—front or backlit





Proofing lights

Output and print zone LED lighting for on-the-fly visual inspection





Media saver

Preserve up to 1 linear meter each time you load a roll



Printer monitoring tools

Improve operational efficiency with the printer status beacon, HP Latex Mobile, 13 HP PrintBeat

Internal print server

Efficiently manage the job queue and settings

Technical specifications

	•		
Printing	Printing modes	27 m²/hr (290 ft²/hr) - High Saturation Backlits (18-pass 6c 230%)	
		44 m²/hr (470 ft²/hr) - Textiles and Canvas	
		(10-pass 6c 170%)	
		77 m²/hr (830 ft²/hr) - Indoor High Quality	
		(6-pass 6c 100%) 120 m²/hr (1290 ft²/hr) - Outdoor	
		(3-pass 6c 80%)	
		180 m²/hr (1950 ft²/hr) - Billboard	
		(2-pass 4c 70%)	
	Print resolution	Up to 1200 x 1200 dpi	
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer	
	Cartridge size	5 liter	
	Color consistency	Maximum color difference (95% of colors)	
	•	\leq 2 dE2000; \leq 1 dE2000 in "Optimize for tiling" mode ¹⁴	
Media	Handling	Roll-to-roll, roll-to-freefall, roll-to-collector,	
		dual-roll, double-sided blockout, double-sided	
	Madiakona	backlit (optional), ink collector (optional)	
	Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas; mesh and porous textiles	
		with optional ink collector	
	Roll size	Single roll up to 3.2 m (126 in)	
		Dual roll up to 2 x 1.6 m (2 x 63 in)	
	Roll weight	Single roll up to 160 kg (350 lb)	
		Dual roll up to 2 x 70 kg (2 x 155 lb)	
	Roll diameter	Up to 30 cm (11.8 in)	
	Thickness	Up to 0.4 mm (0.015 in), by default	
		Up to 2.0 mm (0.08 in), with custom carriage	
		height setting	
	Double-sided	Registration accuracy 5 mm/m (0.06 in/ft),	
	blockout	intended for double-sided PVC blockout banners	
		Registration accuracy of 2 mm (0.08 in), ¹⁵ intended for double-sided backlit outdoor	
	(optional)	advertising applications	
Dimensions	Printer: 598 x 172 x 1	87 cm (235 x 68 x 74 in)	
(w x d x h)	Shipping: 586 x 193 x	216 cm (231 x 76 x 85 in)	
Weight	Printer: 1750 kg (386	0 lb); Shipping: 2510 kg (5530 lb)	
What's in the box	HP Latex 3200 Printe	r, HP 881 Latex Printheads, HP 881 Latex Cleaning	
		(x2), 126-in dual roll spindles (x2), dual roll	
	center support, HP Internal Print Server, HP webcam, documentation		
Environmental	software, user manual, media edge holders (x4), Original HP sample media, media savers (x2), cleaning supplies, spindle supports (x2),		
	pneumatic gun	(xz), cleaning supplies, spinule supports (xz),	
	Standard operating conditions:		
ranges	Temperature: 15 to 3		
	•	Humidity: 20 to 70% RH (non-condensing)	
	Optimal IQ operating conditions:		
		Temperature: 20 to 25°C (68 to 77°F)	
		RH (non-condensing)	
Power consumption	10 kW (typical) - Indoor High Quality mode (6-pass)		
	11 kW (typical) - Outdoor mode (3-pass)		
Certification			
Certincation	Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD and MD compliant,	
		EN60950-1, EN12100-1, FN IS013849-1.	
		EN60950-1, EN12100-1, EN ISO13849-1, EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM)	
	Electromagnetic	EN60204-1, and EN1010-1); Russia, Belarus and	
	Electromagnetic	EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM) Compliant with Class A requirements, including	
	Electromagnetic Environmental	EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM) Compliant with Class A requirements, including USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM),	







Ordering information

Product	1HA06A	HP Latex 3200 Printer	
Accessories	L5E74B	HP Scitex Caldera Grand RIP v11 Software	
	D9Z41A	HP Scitex Onyx Thrive 211 RIP Software	
	M2J33A	HP Latex In-line Slitters	
	J8J14A	HP Latex 3000 Double-sided Day Night Kit	
	Z3R55A	HP Latex 3000 Day Night Edge Holder Kit	
	Z3R56A	HP Latex 3000 Day Night Protector Media	
	CZ065A	HP Latex 3000 Ink Collector Kit	
	F1V49A	HP Latex 3000 Ink Collector Foams Kit	
	1ML40A	HP Latex 3000 Edge Holder Kit	
	CZ059A	HP Latex 126-in Carbon Fiber Spindle	
	G1K80A	HP Latex 126-in Dual Roll Spindle	
	T4E58A	HP Latex Media Saver Kit	
Original HP printheads	CR327A	HP 881 Yellow/Magenta Latex Printhead	
	CR328A	HP 881 Cyan/Black Latex Printhead	
	CR329A	HP 881 Light Magenta/Light Cyan Latex Printhead	
	CR330A	HP 881 Latex Optimizer Printhead	
Original HP ink cartridges and maintenance supplies	CR331A	HP 881 5-liter Cyan Latex Ink Cartridge	
	CR332A	HP 881 5-liter Magenta Latex Ink Cartridge	
	CR333A	HP 881 5-liter Yellow Latex Ink Cartridge	
	CR334A	HP 881 5-liter Black Latex Ink Cartridg	
	CR335A	HP 881 5-liter Light Cyan Latex Ink Cartridge	
	CR336A	HP 881 5-liter Light Magenta Latex Ink Cartridge	
	CR337A	HP 881 5-liter Latex Optimizer Ink Cartridge	
	CR339B	HP 881 Latex Cleaning Roll	
Original HP large format	HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.		
printing	HP Permanent Gloss Adhesive Vinyl REACH ¹⁶		
materials	HP Backlit Polyester Film 🛟 17		
	HP PVC-free Durable Smooth Wall Paper REACH, 16 FSC® certified, 18		
	UL GREENGUARD GOLD Certified ¹⁹		
	HP Premium Poster Paper 🍪 17 FSC® certified 18		
	For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.		
Service kits	1UH14A	HP Latex 3000 Standard Uptime Kit	
	2CA94A	HP Latex 3000 Expert Uptime Kit	
	1VT19A	HP Latex 3000 Maintenance Kit	
	1HA07-67012	HP Latex 3000 Service Maintenance Kit	
	1HA07-67013	HP Latex 3000 Textile Service Maintenance Kit	
	CZ056-67390	HP Latex 3000 Cleaning Kit	
Service contracts	HP Full Hardware Support Contract with Preventive Maintenance and Proactive Monitoring		
	HP Full Hardware Support Contract		

¹⁴ The color variation inside a printed job, when printed with tiling optimized media, has been measured to be with maximum color difference ≤ 1 dE2000 (95% of colors) in "Optimize for tiling" mode when tested on Ahlstrom 5087 wallpaper with stable printing condition within a stable media and a nominal printer. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above the specs mentioned. Backlit substrates measured in transmission mode may yield different results.

HP Shared Maintenance Hardware Support Contract

- Printing double-sided backlit applications requires the optional HP Latex 3000 Double-sided Day Night Kit. Front-to-back image registration accuracy of 2 mm or better when using certified PVC banner and paper media, see https://example.com/go/mediasolutionslocator.
- This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.
- ¹⁷ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.
- 18 BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions.
- ¹⁹ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <u>ul.com/gg</u> or <u>greenguard.org</u>.

